

Jinghong Bathtubs

BPIR Declaration

Version: V1

Designated building product: Class 1

Declaration

Jinghong Pty Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name Jinghong Bathtubs

Identifier JHBT,JHBX Series

Description

The Jinghong Freestanding baths are intended for personal bathing in residential & light commercial applications. The JHBT, JHBX baths are manufactured in vacuum formed white Sanitary Grade Acrylic, fully reinforced with fibreglass & a fully encapsulated particle board base. Sanitary Grade Acrylic features a high gloss surface for ease of cleaning.

Bath Tub sizes: 1500x750x570mm,1500x750x580mm, 1700x800x580mm, 1720x860x580mm.

All sizes are nominal & specific availability varies according to the chosen range (identifier).

Scope of use

The Jinghong bathtubs are intended for use for personal sanitation in residential & light commercial buildings. The BTW freestanding baths must be installed to one wall. Square freestanding bath can be installed to two (corner) or three (alcove) walls, or fully freestanding. Corner Freestanding baths must be installed to corner walls (Left or Right). Freestanding baths must be installed away from adjacent walls. Hot water must be supplied to this sanitary fixture via adjacent tapware.

Conditions of use

The bath must be installed in accordance with our supplied instructions & the relevant requirements of AS/NZS 3500. Ensure that the floor is constructed to support the weight of the bath, full water capacity & the user(s). The tapware & waste must be installed by a Registered Plumber. The maximum temperature of water at the bath outlet is 50 degrees Celsius.

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.2, G12.3.5

Contributions to compliance

- | | |
|-------------------|---|
| B2.3.1(c): | Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, the Jinghong Freestanding Baths have a durability of at least 5 years, when installed and maintained in accordance with our supplied instructions. Englefield Freestanding Baths are designed & manufactured to AS/NZS 2023: 1995 (Baths for ablutionary purposes). |
| F2.3.1: | No materials used in the construction of Jinghong bathtubs give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space. |
| G1.3.2: | The Sanitary Grade Acrylic & mineral-filled polyester resin composite used feature a gloss surface for ease of cleaning. |
| G12.3.5: | Jinghong Vanities must be provided with hot water to satisfy the intended usage of personal bathing (note - tapware not included). |

Supporting documentation

The following additional documentation supports the above statements:

Installation Instructions	Refer website.
Warranty statement(s)	Refer website.
Care & maintenance guide	Refer website.

For further information supporting Jinghong bathtub claims refer to our website.

Contact details

Manufacture location	China
Manufacturer	Jinghong Approved manufacturer
Legal and trading name of importer	Jinghong Pty Ltd
Importer address for service	4F Titoki Place, Albany, Auckland, 0632
Manufacturer/importer website(s)	Jinghong.co.nz
Manufacturer/importer email	sales.jinghong@hotmail.com
Manufacturer/importer phone number	09 441 9098
Manufacturer/importer NZBN	9429036475414