

# Jinghong Slide Showers

## BPIR Declaration

Version: V1

---

### Designated building product: Class 1

---

#### Declaration

Jinghong Pty Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

---

#### Product/system

Name	Jinghong Slide Showers
Identifier	Series JHD, JHX, and JFH

#### Description

The Jinghong JHD, JHX, and JFH series Slide Showers are designed to meet the AS3718 standard. These slide showers are intended for use in both residential and light commercial settings, compatible with mains pressure water supply systems. All models are available in both standard and extended height options. They come with a chrome finish, with some models offering a variety of additional finish options.

---

#### Scope of use

The JHD, JHX, JFH Slide Showers are intended for use with hot & cold water in residential & light commercial applications, with mains pressure water supply systems.

---

## Conditions of use

Jinghong slide showers must be installed by a registered plumber in accordance with the supplied instructions & in compliance with the relevant requirements of AS/NZS 3500 & AS/NZS 6400.

The water supply pipes must be flushed thoroughly to remove any debris. In-line water filters must be used. Recommended working pressure: 35kPa to 500kPa.

If pressure exceeds 500kPa, a pressure limiting valve must be installed. The maximum permitted temperature of water at the outlet is 50 degrees Celsius.

This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the supplied cleaning instructions

---

## Relevant building code clauses

**B2 Durability** — B2.3.1 (c)

**F2 Hazardous building materials** — F2.3.1

**G1 Personal Hygiene** — G1.3.2

**G12 Water Supplies** — G12.3.2, G12.3.5

---

## Contributions to compliance

- |                       |   |
|-----------------------|---|
| <b>B2.3.1(c):</b>     | Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, Jinghong JHD, JHX, JFH Slide Showers have a durability of at least 5 years, when installed and maintained in accordance with our supplied instructions. The Jinghong JHD, JHX, JFH Slide Showers are designed & manufactured to AS/NZS 3718 (Water supply—Tap ware) & are Watermark certified to this standard under Licence no. WMKA20108. |
| <b>F2.3.1:</b>        | No materials used in the construction of Jinghong Slide Showers give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.  |
| <b>G1.3.2:</b>        | Jinghong Slide Showers features chrome, brushed nickel or matt black or gun metal finished surfaces for ease of cleaning.   |
| <b>G12/AS1 2.1.2:</b> | All Jinghong Slide Showers are fit with 2 single check valves for backflow prevention.  |

---

## Supporting documentation

The following additional documentation supports the above statements:

<b>Installation Instructions</b>	Refer website.
<b>Warranty statement(s)</b>	Refer website.
<b>Care &amp; maintenance guide</b>	Refer website.

For further information supporting Jinghong Slide Shower claims refer to our website.

---

## Contact details

<b>Manufacture location</b>	China
<b>Manufacturer</b>	Jinghong Approved manufacturer
<b>Legal and trading name of importer</b>	Jinghong Pty Ltd
<b>Importer address for service</b>	4F Titoki Place, Albany, Auckland, 0632
<b>Manufacturer/importer website(s)</b>	<a href="http://Jinghong.co.nz">Jinghong.co.nz</a>
<b>Manufacturer/importer email</b>	<a href="mailto:sales.jinghong@hotmail.com">sales.jinghong@hotmail.com</a>
<b>Manufacturer/importer phone number</b>	09 441 9098
<b>Manufacturer/importer NZBN</b>	9429036475414